



MATERIAL WARRANTY - MEMBRANE COATING SYSTEM

Globalcote Pty Ltd (ABN: 52 893 030 286) hereby warrants that the Globalcote High Gloss Membrane Coating System will retain its film integrity and not peel, crack or suffer deterioration as a result of faulty manufacture or formulation of the coating system for a period of 10 years from the date of application being **00/00/2012** at **7 Grant Street, Cleveland, QLD, 4163** provided that the following measures have been adhered to:

The surface or substrate is both prepared and coated in accordance with the instructions provided by Globalcote Pty Ltd:

Where the surface or substrate is a TILED ROOF:

- a) **INSPECT** to ensure the whole area is free of loose or missing bedding, damaged tiles and moss/lichen.
- b) **REPAIR OR REPLACE** faulty tiles and defective valley irons.
- c) **CLEAN** the surface using a high pressure cleaner at a minimum 3000psi.
- d) **REBED** ridge capping and replace broken tiles where required.
- e) **REPOINT** all ridge capping using Globalcote Flexible Pointing.
- f) **STERILISE** using Globalcote Surface Treatment at a rate of 6m²/L.
- g) **SURFACE SEALED** with Globalcote Sealer Primer at a rate of 8-10m²/L.
- h) **1st COAT** of Globalcote High Gloss Membrane is applied at rate of 5-6m²/L.
- i) **2nd COAT** of Globalcote High Gloss Membrane is applied at rate of 5-6m²/L.

Where the surface or substrate is a METAL ROOF:

- a) **CLEAN** the surface using a high pressure cleaner at a minimum 3000psi. Ensure rust affected areas are cleaned, rust converted and suitably primed. Ensure any rusty screws are replaced and suitably primed. Ensure flaking paint is removed to provide a sound, clean surface.
- b) **SURFACE SEALED** with Globalcote Sealer Primer at a rate of 8-10m²/L.
- c) **1st COAT** of Globalcote High Gloss Membrane is applied at rate of 5-6m²/L.
- d) **2nd COAT** of Globalcote High Gloss Membrane is applied at rate of 5-6m²/L.

Globalcote Pty Ltd will not be held liable for any loss, damage or costs wholly or partly caused by:

- failure of previous coatings to support the new coatings;
- damage caused by movement, settling, cracking, lifting, peeling, flaking, failure or other deterioration of the substrate;
- damage caused by hydrostatic pressure or entrapped moisture;
- damage caused by maltreatment, such as mechanical damage;
- damage caused by faulty design and/or construction of the premises;
- damage caused by cleaning agents/chemicals or cleaning methods;
- damage caused by fair wear and tear;
- without limitation any other cause outside the reasonable control of Globalcote Pty Ltd;
- negligence by the Applicator, recipient, purchaser/s, or any other associated person;
- failure to maintain surface. Globalcote strongly recommend an annual low pressure wash (800-1000psi).

Where Globalcote Pty Ltd determines that the Globalcote product is faulty, Globalcote will make available free of cost all coating materials required to reinstate the coating system.