



Don't paint it... Globalcote it!
www.globalcote.com.au

PRIMECOTE SEALER PRIMER

Data Sheet

DESCRIPTION

Primecote Sealer Primer is a water based 100% acrylic sealer primer supplied as a milky white substance. When dried the solution appearance becomes a clear film.

FEATURES + BENEFITS

Water Based	Easy application and easy clean up.
Good Adhesion	Ensures the durability of Elastacote Membrane
Fast Dry	Recoat after 2 hours.

TYPICAL PROPERTIES

Gloss Level	Medium	Application	Brush, Roll or Spray
Gloss Level Ind	5 10 20 30 40 50 60 70 80 90 100	Tip Size	517
Colour	Clear	V.O.C	Level < 20 g/L untinted
Number of Coats	1 minimum	Volume Solids (%)	30.6
Touch Dry	30 minutes	Mass Solids (%)	31.3
Recoat	2 hours	Components	1
Full Cure	14 days	Toxicity	Lead free. Dry film is non-toxic.
<i>All figures are quoted at 25 degrees C and 50% Relative Humidity</i>		Wet film per coat	Recommended 100 µm
Coverage	8 - 10 sqm/L	Dry film per coat	Recommended 30 µm
Clean up	Water	Size	5 and 15 litres
Thinner	Not recommended	Shelf life	24 months maximum

APPLICATION PROCESS

Refer to the top coat data sheet.

NOTE: Do not apply where rain is imminent. High humidity may effect curing times. Weather conditions must be considered and deemed suitable before proceeding with application of the Globalcote system .

HEALTH + SAFETY

- Contact Poisons Information Centre (Phone Australia: 13 11 26) or a doctor.
- **Ingestion** Do not induce vomiting. Give water to drink. Seek medical assistance.
- **Eye Contact** Flush eyes in eye baths until irritation subsides. Seek medical assistance.
- **Skin Contact** Wash thoroughly with soap and water. Launder contaminated clothing before reuse. Seek medical assistance if irritations develop.
- **Inhalation** Remove to rest. Seek medical assistance.
- **First Aid facilities** Eyebaths, safety showers
- **Medical Attention** Treat symptomatically.

RECOMMENDATIONS + PRECAUTIONS

- Ensure that appropriate workplace health and safety methods are used when working with this product.
- Use this product in a well ventilated area.
- Ensure that the surface is sound, clean and dry.
- Ensure that the application of the product is in accordance with Globalcote recommendations.
- Due care and consideration should be taken where water collection methods are present. Globalcote recommends allowing 10 days curing and an initial rinse (rain or tap water wash) prior to reconnecting water collection systems.

MSDS: Available on request. Please visit the Globalcote Website - www.globalcote.com.au.

DISCLAIMER The recommendations and data provided in this document are true and accurate at the time of testing. The information is given in good faith but without any guarantee as conditions and methods of use on the Globalcote product are beyond Globalcote's control. Globalcote recommends that the applicator of this product determines the suitability of the Globalcote material and its recommendations prior to use or application.